



SmartView+

Features

- Fully SMETS Compliant
- Modular HAN supports Zigbee or WMBus
- Full Colour QVGA Dot Matrix Display
- Automatic Single or Dual Fuel Modes
- Automatic Credit & Pre-Payment Modes
- Full PPMID Functionality
- Current & Next Tariff
- Customised Usage Targets
- Detailed Usage History
- OTA Upgradeable Firmware & UI
- Customised Interface Options
- Clear & Intuitive User Interface
- GUI with Simple Language & Icons
- Ambient Alert Illumination
- Adjustable Backlight & Standby Mode
- Tactile & Intuitive Button Layout
- Internal Rechargeable Battery
- Enhanced Messaging Function
- Free Standing Unit
- Standby "Energy Clock"
- Water Resistant
- Displays 13 Months of Data

Tech Specs

- SmartView+**
- Display Type: Transmissive Active Matrix TFT
 - Screen Resolution: 240x320 Dots
 - Screen Size: 2.8in (diagonal)
 - Display Brightness (max): 4000Cd/m²
 - Display Viewing Angle: 60° bottom, 70° top, left, right
 - Sounder Volume @ 10cm: -85dB
 - Sounder Frequency: 2.7kHz
 - Standby Time on Battery (max): 130 hours (approx.)
 - Operating Time on Battery (typical): 7 hours (approx.)
 - DC Supply Voltage: 5V
 - DC Power Consumption (charging): 2W
 - TX Power (max): 10mW erp
 - Product Weight: ~135 grams
 - Product Dimensions: 107mm x 61mm x 61mm
 - Operating Temperature: 0-45
- SmartView+ Battery**
- Battery Type: ICR14500 liIon rechargeable
 - Battery Capacity: 750mAh, 3.7V
- SmartView+ AC Adapter**
- AC Adapter (input): 100V-240VAC, 0.15A
 - AC Adapter (output): 5V, 1A
 - Frequency Range: 2.394GHz - 2.507GHz